

2009115-030502

UNITED STATES PATENT APPLICATION

OF

HEUME IL BAEK

FOR

A GAMMA REFERENCE VOLTAGE GENERATING CIRCUIT

AND A METHOD OF USING THE SAME

IN A LIQUID CRYSTAL DISPLAY

[0001] This application claims the benefit of Korean Patent Application No. P2001-11776 filed in Korea on March 7, 2001, which is hereby incorporated by reference.

BACKGROUND OF THE INVENTION

FIELD OF THE INVENTION

[0002] The present invention relates to a display device, and more particularly, to a gamma reference voltage generating circuit and a method of using a gamma reference voltage generating circuit in a liquid crystal display. Although the present invention is suitable for a wide scope of applications, it is particularly suitable for obtaining an optimized luminance in a transmissive mode and a reflective mode.

DISCUSSION OF THE RELATED ART

[0003] A gamma reference voltage generating circuit of a liquid crystal display is an essential element of the liquid crystal display that influences picture quality. The gamma reference voltage generating circuit generates and outputs a reference voltage required for digital/analog conversion in a source driving circuit.

[0004] FIG. 1 illustrates the structure of a liquid crystal display device according to the related art. In FIG. 1, the liquid crystal display device includes a liquid crystal display 11, a gate driving circuit 12, a source driving circuit 13, and a gamma reference voltage generator 14. The liquid crystal display panel 11 includes a plurality of gate lines arranged

at fixed intervals along a first direction, and a plurality of data lines arranged at fixed intervals along a second direction orthogonal to the gate lines, thereby forming a pixel region in a matrix array. The gate driving circuit 12 outputs a pulse signal, which sequentially scans pixels of the liquid crystal display panel 11 column by column. The source driving circuit 13 converts externally input red (R), green (G), and blue (B) digital video signals into analog signals, and outputs the converted video signals to each of the plurality of data lines. In order to convert the R, G, and B digital video signals into analog signals, a digital/analog conversion is performed using a reference voltage output from the gamma reference voltage generator 14, thereby generating a liquid crystal driving voltage. The generated liquid crystal driving voltage is applied to the plurality of data lines of the liquid crystal display panel during each scan.

[0005] The gamma reference voltage generator 14 serially connects a plurality of resistors between a power terminal Vdd and a ground terminal, thereby supplying a divided voltage. Furthermore, the gamma reference voltage generator 14 generates and outputs the reference voltage necessary for converting the digital video signals at the source driving circuit 13.

[0006] FIG. 2 shows a block diagram of a source driving circuit according to the related art. In FIG. 2, the source driving circuit includes a shift register 1 outputting a latch clock signal, a first latch unit 2 respectively latching R, G, and B digital video data signals, which are sequentially synchronized with clock signals of a timing controller (not shown),

and converting a timing system signal of a dot-at-a-time scanning into a line-at-a-time scanning in accordance with the latch clock signal output from the shift register 1, a second latch unit 3 latching data stored in the first latch unit 2 at every horizontal line cycle in accordance with a transfer enable signal, a digital/analog converter 4 converting the data latched by the second latching unit 3 into analog signals in accordance with the gamma reference voltage, and a buffer 5 buffering the analog signals output from the digital/analog converter 4 and outputting the signals to each data line.

[0007] Since the picture quality of the liquid crystal display is highly dependent upon the gamma reference voltage, the gamma reference voltage should be determined based on the electro-optical characteristics of the liquid crystal display panel. A liquid crystal display may be classified, based upon the backlight device used, into a transmissive mode, a semi-transmissive mode, and a reflective mode. The semi-transmissive mode of the liquid crystal display may perform either of two different driving modes depending on the operating conditions. More specifically, a first driving mode includes the reflective mode using a peripheral light source, and a second driving mode includes the transmissive mode using a backlight source. However, due to differences in transmission and reflection characteristic curves of the two driving modes, luminance of the liquid crystal display may vary depending on external conditions, thereby deteriorating picture quality.

[0008] FIG. 3 shows a luminance curve of the transmissive mode and the reflective mode according to the related art. In FIG. 3, the luminance value of the transmissive and the reflective modes may be explained by using the following equations:

$$\begin{aligned} L^* &= 116(Y/Y_{MAX})^{1/3} - 16 & \text{for } Y/Y_{MAX} > 0.008856 \\ L^* &= 903.3(Y/Y_{MAX}) & \text{for } Y/Y_{MAX} \leq 0.008856 \end{aligned}$$

where L^* represents the luminance value considered the human visual characteristic, Y represents the luminance value at gray scales, and Y_{MAX} represents the maximum luminance value.

[0009] The gamma reference voltage is determined by generating a gray voltage in accordance with the maximum luminance value Y_{MAX} . More specifically, as shown in FIG. 3, when using the source driving circuit that displays 64 gray scales, the difference in L_T values between each gray scale is about 1.25 $((100-20)/64)$ in the transmissive mode and about 1.0937 $((100-30)/64)$ in the reflective mode. Therefore, a middle gray scales (*i.e.*, 32 gray scales) can be described by using the following equations:

$$L_T(X) = 1.25 \times X + 20$$

$$L_R(X) = 1.0937 \times X + 30$$

where X is the number of gray scales.

[0010] The L_T value is about 60 in the transmissive mode, and the L_R value is about 64.9 in the reflective mode. In such cases, as shown in FIG. 3, the driving voltage is 2.2V in the transmissive mode and 2.35V in the reflective mode. Accordingly, a difference in driving voltage occurs between the transmissive mode and the reflective mode in an identical gray scale, which is the middle gray in this case. Therefore, when the transmissive mode and the reflective mode are operated with the same gamma voltage circuit, differences occur in the gray scale that is actually realized. Accordingly, the gamma reference voltage circuit of a liquid crystal display according to the related art has the following disadvantages.

When determining a gamma reference voltage according to a difference in luminance in the reflective mode and the transmissive mode, either a compensated value of the two curves or a design value of a compensating film used in designing the panel was modified. However, such solutions are insufficient for determining the gamma reference voltage value in the liquid crystal display panel.

SUMMARY OF THE INVENTION

[0011] Accordingly, the present invention is directed to a gamma reference voltage generating circuit in a liquid crystal display that substantially obviates one or more problems due to limitations and disadvantages of the related art.

[0012] An object of the present invention is to provide a gamma reference voltage generating circuit and a method of using a gamma reference voltage generating circuit in a liquid crystal display that determines a gamma reference voltage by applying the luminance of both a transmissive mode and a reflective mode.

[0013] Another object of the present invention is to provide a gamma reference voltage generating circuit and a method of using a gamma reference voltage generating circuit in a liquid crystal display to enhance the picture quality of the liquid crystal display.

[0014] Additional features and advantages of the invention will be set forth in the description which follows, and in part will be apparent from the description, or may be learned by practice of the invention. The objectives and other advantages of the invention will be realized and attained by the structure particularly pointed out in the written description and claims hereof as well as the appended drawings.

[0015] To achieve these objects and other advantages with the purpose of the present invention, as embodied and broadly described, a gamma reference voltage generating circuit in a liquid crystal display includes a first gamma power unit outputting a first gamma voltage for a reflective driving mode of the liquid crystal display, a second gamma power unit outputting a second gamma voltage for a transmissive driving mode of the liquid crystal display, and a switching unit selecting one of the first gamma voltage of the first gamma power unit and the second gamma voltage of the second gamma power unit, and outputting the selected gamma voltage to a source driving circuit.

2025.11.16 15:03:52

[0016] In another aspect of the present invention, a gamma reference voltage generating circuit in a liquid crystal display includes a DC/DC converter generating a first power V_{DD1} and a second power V_{DD2} for one of a reflective driving mode and a transmissive driving mode, a switching unit selecting and outputting one of the first power and the second power, a first gamma power unit inputting the first power from the switching unit and outputting a first gamma power, a second gamma power unit inputting the second power from the switching unit and outputting a second gamma power, a first common power unit inputting the first power from the switching unit and outputting a first common voltage; and a second common power unit inputting the second power from the switching unit and outputting a second common voltage.

[0017] In another aspect, a liquid crystal display device includes a liquid crystal display panel, a source driving circuit connected to the liquid crystal display panel, a gate driving circuit connected to the liquid crystal display panel, a first output unit producing a first voltage during a reflective driving mode of the liquid crystal display panel, a second output unit producing a second voltage during a transmissive driving mode of the liquid crystal display panel, and a switching unit selecting one of the first and second voltages, and outputting the selected voltage to the source driving circuit.

[0018] In another aspect, a method for generating a reference voltage for digital/analog conversion in a source driving circuit of a liquid crystal display device includes providing a first voltage during a reflective driving mode of the liquid crystal display device, providing

a second voltage during a transmissive driving mode of the liquid crystal display, selecting one of the first and second voltages, and providing the selected voltage to the source driving circuit.

[0019] It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

[0020] The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this application, illustrate embodiments of the invention and together with the description serve to explain the principle of the invention. In the drawings:

[0021] FIG. 1 shows a liquid crystal display according to the related art;

[0022] FIG. 2 shows a detailed block diagram of a source driving circuit according to the related art;

[0023] FIG. 3 shows luminance curves according to the transmissive mode and the reflective mode of a liquid crystal display according to the related art;

[0024] FIG. 4 illustrates an exemplary gamma reference voltage generating circuit of a liquid crystal display according to the present invention;

[0025] FIGs. 5A and 5B illustrate a signal diagram of a driving voltage range in an exemplary liquid crystal display according to the present invention; and

[0026] FIG. 6 illustrates another exemplary gamma reference voltage generating circuit of a liquid crystal display according to the present invention.

DETAILED DESCRIPTION OF THE INVENTION

[0027] Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numbers will be used throughout the drawings to refer to similar parts.

[0028] FIG. 4 illustrates an exemplary gamma reference voltage generating circuit of a liquid crystal display according to the present invention that drives reflective and transmissive modes with different driving voltages. In FIG. 4, the gamma reference voltage generating circuit may include a first gamma power unit 14a providing a gamma power in the reflective mode, a second gamma power unit 14b providing a gamma power in the transmissive mode, a switching unit 15 selecting an output voltage of the first and second gamma power units 14a and 14b, and a buffer 16 buffering power output from the switching unit 15 and outputting the buffered power to the source driving circuit. The first gamma power unit 14a and the second gamma power unit 14b may each be formed of a different divided voltage resistance, or power voltage Vdd.

20250925 15:53:53

[0032] FIG. 6 illustrates another exemplary gamma reference voltage generating circuit of a liquid crystal display according to the present invention. In FIG. 6, the gamma reference voltage generating circuit may include a DC/DC converter 21 generating various voltages (V_{DD1} , V_{DD2} , V_{GH} , V_{GL} , and V_{REF}) applied in a liquid crystal display by using a voltage input from a driving system, a switching unit 22 selecting either a first power voltage V_{DD1} or a second power voltage V_{DD2} diverged from the DC/DC converter 21, first and second common power units 25a and 25b each providing a different common voltage to the liquid crystal display panel in accordance with the voltage output from the switching unit 22, first and second gamma power units 23 and 24 each outputting a gamma voltage corresponding to either a reflective mode or a transmissive mode to a digital/analog converter of a source driving circuit in accordance with the voltage output from the switching unit 22, a buffer 26 buffering a reference voltage generated from the first and the second gamma power units 23 and 24 and outputting the buffered voltage to the source driving circuit, and a source driving circuit 27 whereby the buffered reference voltage is applied.

[0033] In the gamma reference voltage generating circuit of FIG. 6, a stable gamma reference voltage may be generated even though the driving voltage ranges of the reflective mode and the transmissive mode are different. Due to the difference in driving voltage range between the reflective mode and the transmissive mode, the DC/DC converter may use a voltage diverged from a liquid crystal module of the driving system to generate the first power voltage V_{DD1} and the second power voltage V_{DD2} . Additionally,

the switching unit 22 applies the first and the second power voltages V_{DD1} and V_{DD2} to the first or the second gamma power unit 23 or 24, and simultaneously applies the two power voltages to the first and the second common power units 25a and 25b in accordance with the reflective mode and the transmissive mode. The signals may be synchronized with the ON/OFF switch of the backlight source. Therefore, in the reflective mode, the switching unit 22 simultaneously applies the first power voltage V_{DD1} to the first gamma voltage unit 23 and to the first common voltage unit 25a. In the transmissive mode, the switching unit 22 simultaneously applies the second power voltage V_{DD2} to the second gamma power unit 24 and to the second common power voltage unit 25b.

[0034] Each of the first and the second gamma power units 23 and 24 may apply a different gamma reference voltage to the source driving circuit according to the corresponding driving mode. Each of the first and the second common power units V_{COM1} and V_{COM2} may also input a different power V_{DD1} or V_{DD2} . Therefore, according to the selection of power V_{DD1} or V_{DD2} , the common power V_{COM1} or V_{COM2} may be selected without any additional switches.

[0035] Reference voltage generated from the gamma power unit passes through the buffer to be outputted to the digital/analog converter.

[0036] It will be apparent to those skilled in the art than various modifications and variations can be made the gamma reference voltage generating circuit of the present invention without departing from the spirit or scope of the invention. Thus, it is intended

that the present invention cover the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

2025-09-16 10:00:00